

LOGZILLA DOCUMENTATION

Outgoing Webhooks

Send LogZilla trigger events to Slack, PagerDuty, or any HTTP endpoint using GET or POST webhooks with JSON payload templates and event variable substitution

Alerts · Generated June 12, 2026 · logzilla.ai/docs/alerts/outgoing-webhooks

The Webhook option in the trigger menu allows users to send a `GET` or `POST` webhook command to a northbound server such as [slack.com](http://www.slack.com) (<http://www.slack.com>)

The example below shows a trigger set to match `rejected` messages from Postfix. When the trigger matches, it will post to a Slack channel automatically.

Webhook Post to Slack

Edit trigger



Name *

Postfix: Email Rejected

Event match

rejected

More ▾

✱ Reset

Actions

Mark as

Actionable

Non-Actionable



Send e-mail



Send webhook

Method

Webhook endpoint *

POST ▾

https://hooks.slack.com/services/T02REDEN

URL of remote webhook endpoint. Only **HTTP** and **HTTPS** URLs are supported.

Message template *

View available placeholders ▶

```
1 | {
2 |   "channel": "#logzilla-alerts",
3 |   "attachments": [
4 |     {
5 |       "color": "#9C1A22",
6 |       "title": "Alert from {{event:host}}",
7 |       "text": "``{{event:message}}``",
8 |       "thumb_url": "http://www.logzilla.net/images
```

Requests are sent with **Content-Type: application/json**

Skip SSL verification

Untrusted certificates may not be secure


Public


Cancel

Save changes

Alert Shown in Slack Channel

11:49 ☆ LogZilla Triggered an alert on s[REDACTED]

 LogZillaBot

Alert from staging 

0AE09A004B: to=<[REDACTED]@logzilla.et>, relay=email-smtp.us-east-1.amazonaws.com[107.20.176.109]:25, delay=0.64, delays=0/0/0.34/0.3, dsn=5.0.0, status=bounced (host email-smtp.us-east-1.amazonaws.com[107.20.176.109] said: 554 Message rejected: Email address is not verified. The following identities failed the check in region US-EAST-1: [REDACTED]@logzilla.et, Mail Delivery System <[REDACTED]@logzilla.et> (in reply to end of DATA command))

Program	Severity
smtp	INFO

Post Data Used

The Trigger above uses the following JSON:

```
{
  "channel": "#logzilla-alerts",
  "attachments": [
    {
      "color": "#9C1A22",
      "title": "Alert from {{event:host}}",
      "text": "```${event:message}```",
      "thumb_url": "http://www.logzilla.net/images/icon_warning_25x25.png",
      "fallback": "Alert from {{event:host}}",
      "author_icon": "http://www.logzilla.net/images/log_file_icon_25x25.png",
      "pretext": "LogZilla Triggered an alert on {{event:host}}",
      "author_link": "mailto:support@logzilla.net",
      "fields": [
        {
          "value": "{{event:program}}",
          "title": "Program",
          "short": "true"
        },
        {
          "value": "{{event:severity}}",
          "short": "true",
          "title": "Severity"
        }
      ]
    },
    {
      "text": "Alert from {{event:host}}",
      "fields": [
        {
          "value": "{{event:program}}",
          "title": "Program",
          "short": "true"
        },
        {
          "value": "{{event:severity}}",
          "short": "true",
          "title": "Severity"
        }
      ]
    }
  ],
  "mrkdwn_in": [
    "text",
    "fields"
  ],
  "author_name": "LogZillaBot"
}
```

```
    }  
  ],  
  "username": "logzilla-bot",  
  "icon_url": "http://www.logzilla.net/images/logo_orange_png_cropped_40x40.png"  
}
```